



## TV series | TV 110

Vertical drive systems

### APPLICATIONS

#### // Warehouse trucks

Pallet trucks, Stackers,

#### // AGV / AGC

AGVs,

#### // Electric vehicles

Mobility, Hospital,

### AVAILABLE OPTIONS

#### drive unit tv 110

- Max wheel torque in acceleration 400 Nm
- Max wheel torque continuously 160 Nm
- Max load on the gearbox 1200 kg
- Gear ration up to 1/32.2

#### wheel size

- Ø 230 x 75 mm

#### traction motor

- Type AC, DC
- Voltage starting from 24V
- Power up to 2 kW

#### brake

- Electromagnetic
- Voltage starting from 24V
- Static brake torque up to 12 Nm
- Hand release lever available

#### steering options

- Manual, with different mounting options
- Electrical, with pinion and crown

#### power steering unit

- Type AC, DC, PM
- Voltage from 24V to 48V
- Power 0.5 kW
- Output torque 60 Nm

#### plate

### Benefits

- Widespread drive unit in materials handling sector
- Two options for tiller attachment
- The version with fixed motor prevents the risk of wiring damage
- Low noise ground gears
- Reduced backlash
- Fully oil lubricated gearbox
- Possibility of full integration with traction motor, steering system, plate and electronics
- High efficiency 95%
- 100% tested and certified drive system
- Wide range of wheels
- Wide range of motors
- Easy maintenance
- ISO9001 and ISO14001 certified
- Made in Italy

Available with set up for:

- Potentiometer pinion
- Position proxy
- Mechanical stop

