



TVO series | TVO 110

- Compact gearboxes, ideal for electric undercarriages
- Horizontal installation in the track
- Low noise ground gears
- Low backlash gears
- Fully oil lubricated gearboxes
- High efficiency, about 95%
- 100% tested and certified drive systems
- Wide range of motors
- Easy maintenance
- ISO9001 and ISO14001 certified production system
- Made in Italy

APPLICATIONS

// Undercarriage

Undercarriage,

// Electric vehicles

Mobility, Airport, Air platforms, Any other,

AVAILABLE OPTIONS

drive unit tvo-110

- Max wheel torque in acceleration 400 Nm
- Continuous wheel torque 160 Nm
- Max load on the gearbox 1000 kg
- Gear ratio 1/28.9

wheel sizes

- Ø 230 X 75 mm

traction motor

- Type AC
- Voltage 24V - 48V
- Power 1,2 kW
- Speed 3525 rpm

brake

- Electromagnetic
- Voltage 24V – 48V
- Static brake torque 12 Nm
- Hand release lever available

Benefits

- Wide performance range
- High load capacity
- Installation space savings
- Easy fixing to the chassis
- High efficiency, low energy consumption
- Reduced backlash, low noise precision gearing
- Fully oil lubricated gearbox
- Wide range of motors
- Selectable gear ratio
- Different brake size also available with release lever
- 100% tested and certified drive system
- ISO9001, ISO14001, ISO18001 certified
- Made in Italy

